


ASSEMBLY INSTRUCTIONS



Marine Large Flush Mount

Item # SL 4002

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.


TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver

Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove metal shade (K) from fixture body (D) by removing screws (L).
3. Remove mounting plate (A) from fixture body (D) by removing cap nuts (E).
4. Install mounting plate (A) to the junction box and secure with the mounting screws (C).
5. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut (M).
- NOTE:** It is imperative that the fixture is grounded.
6. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut (M).
7. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut (M).
- CAUTION:** Do not reverse the hot and neutral connections.
8. Make sure all wire connections are tight, then carefully tuck into the junction box.
9. Install fixture body (D) to mounting plate (A) and secure with cap nuts (E).

ASSEMBLY INSTRUCTIONS



Marine Large Flush Mount

Item # SL 4002

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

10. Install light bulbs into the sockets.
 11. Open glass ring (**G**) by removing latch (**H**) (see diagram 2).
 12. Remove set screws (**F**) from glass ring (**G**) using provided allen wrench (**J**), then install glass shade (**I**) to glass ring (**G**) and secure with set screws (**F**) using provided allen wrench (**J**).
- NOTE:** Do not over-tighten otherwise glass could become damaged.
13. Close glass ring (**G**) by securing latch (**H**).
 14. Install metal shade (**K**) to fixture body (**D**) and secure with screws (**L**).

Care Instructions: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.